


OFFICIAL QUOTE

25KVA 240 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER





25KVA 240 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER

\$2,490.20 CAD


Single Phase Autotransformer with a capacity of 25kVA, transforming 240 Volts to 110 Volts

SKU: MC25C-A2

Categories: <u>Autotransformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Single Phase Autotransformer with a capacity of 25kVA, transforming 240 Volts to 110 Volts



OFFICIAL QUOTE

25KVA 240 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER



PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 146.8 lbs |
| Phases | 1 |
| kVA | <u>25</u> |
| Connection | <u>1PhA-NT-1</u> |
| Primary Voltage | 240 |
| Primary Max Current | 60.1A |
| Primary Markings | <u>H0-H1</u> |
| Primary Terminals | #2-14 AWG |
| Secondary Voltage | 110 |
| Secondary Max Current | 131.2A |
| Secondary Markings | <u>X0-X1</u> |
| Secondary Terminals | 300MCM-6 |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | 10kV |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.5 - 3.5% |
| Sound (db) | 45 dB |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-4</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

25KVA 240 VOLTS TO 110 VOLTS SINGLE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|