


OFFICIAL QUOTE

150KVA 460 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER





150KVA 460 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER


\$4,341.10 CAD


Three Phase Autotransformer with a capacity of 150kVA, transforming 460Y Volts to 575Y Volts

SKU: RC150H1-J1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 150kVA, transforming 460Y Volts to 575Y Volts



OFFICIAL QUOTE





PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 224 lbs |
| Phases | <u>3</u> |
| kVA | <u>150</u> |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 460 |
| Primary Max Current | 188.3A |
| Primary Markings | <u>X1-X2-X3</u> |
| Primary Terminals | 600MCM-2 |
| Secondary Voltage | <u>575</u> |
| Secondary Max Current | 150.6A |
| Secondary Markings | <u>H1-H2-H3</u> |
| Secondary Terminals | 300MCM-6 |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>0.5 - 1.5%</u> |
| Sound (db) | 45 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-6</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

150KVA 460 VOLTS TO 575 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|