



## 25KVA 110 VOLTS TO 416 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

**\$3,810.24 CAD**

Single Phase Isolation Transformer with a capacity of 25kVA, transforming 110 Volts to 416 Volts

SKU: SC25A2-G/Z3

Categories: [Isolation Transformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Single Phase Isolation Transformer with a capacity of 25kVA, transforming 110 Volts to 416 Volts



PRODUCT SPECIFICATIONS

Weight	225 lbs
Phases	<a href="#">1</a>
kVA	<a href="#">25</a>
Connection	<a href="#">1Ph-2coil-5T-SU</a>
Primary Voltage	<a href="#">110</a>
Primary Max Current	<a href="#">227.27A</a>
Primary Markings	<a href="#">X1-X2</a>
Primary Terminals	<a href="#">600 MCM – 2</a>
Secondary Voltage	<a href="#">416</a>
Secondary Max Current	<a href="#">60.1A</a>
Secondary Markings	<a href="#">H1-H2</a>
Secondary Terminals	<a href="#">600 MCM – 2</a>
Primary Taps	<a href="#">+/- 2 x 2.5%</a>
Conductor Material	<a href="#">Copper</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">98.00% (DOE 2016/NRCAN 2019)</a>
Impedance Range	<a href="#">4.0 – 6.0%</a>
Sound (db)	<a href="#">45</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-6</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>
Temperature Rise	<a href="#">150°C</a>



OFFICIAL QUOTE

25KVA 110 VOLTS TO 416 VOLTS  
SINGLE PHASE ISOLATION  
TRANSFORMER



Insuation Class	<a href="#">150°C</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>