



150KVA 200 VOLTS TO 460 VOLTS THREE PHASE AUTOTRANSFORMER

\$7,277.80 CAD

Three Phase Autotransformer with a capacity of 150kVA, transforming 200Y Volts to 460Y Volts

SKU: RA150B1-H1

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 150kVA, transforming 200Y Volts to 460Y Volts



PRODUCT SPECIFICATIONS

Weight	555 lbs
Phases	3
kVA	150
Connection	3PhA-NT-1
Primary Voltage	200
Primary Max Current	433A
Primary Markings	X1-X2-X3
Primary Terminals	Pads
Secondary Voltage	460
Secondary Max Current	188.3A
Secondary Markings	H1-H2-H3
Secondary Terminals	600MCM-2
Primary Taps	N/A
Conductor Material	Aluminum
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	1.5 – 3.5%
Sound (db)	55
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-8
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
150KVA 200 VOLTS TO 460 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------