



9KVA 416 VOLTS TO 110 VOLTS THREE PHASE AUTOTRANSFORMER


\$1,585.41 USD

Three Phase Autotransformer with a capacity of 9kVA, transforming 416Y Volts to 110Y Volts

SKU: RC9G-A2

Categories: [Autotransformer](#)

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 9kVA, transforming 416Y Volts to 110Y Volts



PRODUCT SPECIFICATIONS

Weight	48 lbs
Phases	3
kVA	9
Connection	3PhA-NT-1
Primary Voltage	416
Primary Max Current	12.5A
Primary Markings	H1-H2-H3
Primary Terminals	Terminal Blocks
Secondary Voltage	110
Secondary Max Current	47.2A
Secondary Markings	X1-X2-X3
Secondary Terminals	#2-14 AWG
Primary Taps	N/A
Conductor Material	Copper
Insulation Class	220°C (Class H)
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	N/A
Impedance Range	2.5 – 4.5%
Sound (db)	40
Enclosure Type	NEMA 1
Enclosure Size	E1-3
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE
9KVA 416 VOLTS TO 110 VOLTS
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer	Canada/RPM
----------------------	----------------------------