





CE150H-A \$182.00 CAD

SKU: 8b94609605b3 Categories: <u>Control Transformers</u>

PRODUCT SPECIFICATIONS

Weight	5 lbs
Phases	1
VA	<u>150</u>
Connection	<u>1Ph-CT-SS-SU</u>
Primary Voltage	<u>480</u>
Primary Max Current	<u>0.31A</u>

The quote is valid 30 days from 30 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





Primary Markings	<u>H1-H2</u>
Primary Terminals	Leads
Secondary Voltage	120
Secondary Max Current	<u>1.25A</u>
Secondary Markings	<u>X1-X2</u>
Secondary Terminals	Leads
Primary Taps	N/A
Conductor Material	Copper
Temperatue Rise	<u>80°C</u>
Insuation Class	<u>130°C</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency	N/A
Impedance	<u>5.0 – 7.0%</u>
Sound (db)	<u>40</u>
Enclosure Type	<u>Type-1 Indoor</u>
Enclosure	See Chart
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered
Finish	<u>Semigloss – BlackSemigloss – Black</u>