

OFFICIAL QUOTE

3KVA 208 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER





3KVA 208 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER


\$861.69 USD


Three Phase Autotransformer with a capacity of 3kVA, transforming 208Y Volts to 115Y Volts

SKU: RC3B-A1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 3kVA, transforming 208Y Volts to 115Y Volts



OFFICIAL QUOTE



3KVA 208 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 20 lbs |
| Phases | <u>3</u> |
| kVA | 3 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 208 |
| Primary Max Current | <u>8.3A</u> |
| Primary Markings | H1-H2-H3 |
| Primary Terminals | Terminal Blocks |
| Secondary Voltage | 115 |
| Secondary Max Current | <u>15.1A</u> |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | Terminal Blocks |
| Primary Taps | N/A |
| Conductor Material | Copper |
| Insulation Class | 180°C (Class F) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | 1.5 - 3.5% |
| Sound (db) | 40 |
| Enclosure Type | NEMA 1 |
| Enclosure Size | <u>E1-1</u> |
| Finish/Colour | Polyester Powder Coat - ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

3KVA 208 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|