



OFFICIAL QUOTE









30KVA 480 VOLTS TO 208Y/120 VOLTS THREE PHASE BOLT-ON BREAKER MINI POWER CENTER

\$13,665.00 CAD

SKU: MP3A30H-M/BO/CLC
Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES







OFFICIAL QUOTE



30KVA 480 VOLTS TO 208Y/120 VOLTS THREE PHASE BOLT-ON BREAKER MINI POWER CENTER

PRODUCT SPECIFICATIONS

Weight	710 lbs
Phases	<u>3</u>
kVA	30
Connection	MPC3P-5t
Primary Taps	<u>+/- 2 x 2.5%</u>
Conductor Material	<u>Aluminum</u>
BIL (Insulation) Level	10kV
Impedance Range	1.5 - 3.0%
Enclosure Type	NEMA 3R Outdoor
Enclosure Size	E3R-1PMPC-3B
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E495724, ISO 9001:2015 Registered
Incoming Voltage	480
Primary Breaker	<u>80A</u>
Interruping Rating	14kAIC @ 480V
Output Voltage	<u>208Y/120</u>
Secondary Breaker	100A
Short Circuit Withstand	10kAIC @ 240V
Panel Board	Bolt-On
Load Center Bus Material	<u>Copper</u>
# of Circuits	30
Circuit Breaker Suitability	Eaton Type BAB
Temperatue Rise	130°C



OFFICIAL QUOTE



30KVA 480 VOLTS TO 208Y/120 VOLTS THREE PHASE BOLT-ON BREAKER MINI POWER CENTER

Insuation Class	200°C (Class N)
Country/Manufacturer	<u>Canada/RPM</u>