



BC112H-N1/EP \$18,593.66 USD

SKU: e082dda2ee1d Categories: <u>Encapsulated Isolation Transformer</u>

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





PRODUCT SPECIFICATIONS

| Weight | 1365 lbs |
|---------------------|---------------------|
| Phases | <u>3</u> |
| kVA | <u>112.5</u> |
| Connection | <u>3Ph-DY-5T-SD</u> |
| Primary Voltage | <u>480</u> |
| Primary Max Current | <u>135.3A</u> |
| Primary Markings | <u>H1-H2-3</u> |
| Primary Terminals | <u>300MCM-6</u> |

The quote is valid 30 days from 3 May 2025. The price does not include: "Special Features", freight and possible taxes.

Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.





| Secondary Voltage | <u>400Y/231</u> |
|----------------------------|---|
| Secondary Markings | <u>X0-X1-X2-X3</u> |
| Secondary Terminals | <u>300MCM-6</u> |
| Primary Taps | <u>+/-2 x 2.5%</u> |
| Conductor Material | <u>Copper</u> |
| Temperatue Rise | <u>130°C</u> |
| Insuation Class | <u>200°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency | N/A |
| Impedance | <u>1.5 – 3.5%</u> |
| Sound (db) | <u>50</u> |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure | E3R-3PEP-8 |
| Finish | Polyster Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |