


#### **OFFICIAL QUOTE**

### 330KVA 240 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER





# 330KVA 240 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER


\$19,075.59 USD

Single Phase Isolation Transformer with a capacity of 330kVA, transforming 240 Volts to 415 Volts

**SKU:** SC330C-G2/Z3

**Categories:** <u>Isolation Transformers</u>

### **SCHEMATIC/DIAGRAM AND DIMENSION PICTURES**





Single Phase Isolation Transformer with a capacity of 330kVA, transforming 240 Volts to 415 Volts



### **OFFICIAL QUOTE**



# 330KVA 240 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

#### PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Weight	1720 lbs
Phases	1
kVA	330
Connection	1Ph-2coil-5T-SU
Primary Voltage	240
Primary Max Current	1375.0A
Primary Markings	<u>X1-X2</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	415
Secondary Max Current	795.18A
Secondary Markings	H1-H2
Secondary Terminals	<u>Pads</u>
Primary Taps	+/- 2 x 2.5%
Conductor Material	Copper
BIL (Insulation) Level	10kV
Efficiency (@35% Load) %	98.90% (DOE 2016/NRCan 2019)
Impedance Range	4.0 - 6.0%
Sound (db)	<u>55</u>
Enclosure Type	NEMA 3R Indoor
Enclosure Size	E3R-9S
Finish/Colour	Polyester Powder Coat - ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered
Temperatue Rise	150°C



### **OFFICIAL QUOTE**



# 330KVA 240 VOLTS TO 415 VOLTS SINGLE PHASE ISOLATION TRANSFORMER

Insuation Class	150°C
Country/Manufacturer	Canada/RPM
Finish/Colour	Polyester Powder Coat – ANSI/ASA 61 Grey