



**112KVA 347 VOLTS TO 110 VOLTS  
THREE PHASE AUTOTRANSFORMER**



**112KVA 347 VOLTS TO 110  
VOLTS THREE PHASE  
AUTOTRANSFORMER**


**\$4,793.55 USD**

Three Phase Autotransformer with a capacity of 112.5kVA, transforming 347Y Volts to 110Y Volts

**SKU:** RA112E-A2

**Categories:** [Autotransformer](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Autotransformer with a capacity of 112.5kVA, transforming 347Y Volts to 110Y Volts



## PRODUCT SPECIFICATIONS

Weight	494 lbs
Phases	<a href="#">3</a>
kVA	<a href="#">112.5</a>
Connection	<a href="#">3PhA-NT-1</a>
Primary Voltage	<a href="#">347</a>
Primary Max Current	<a href="#">187.2A</a>
Primary Markings	<a href="#">H1-H2-H3</a>
Primary Terminals	<a href="#">600MCM-2</a>
Secondary Voltage	<a href="#">110</a>
Secondary Max Current	<a href="#">590.5A</a>
Secondary Markings	<a href="#">X1-X2-X3</a>
Secondary Terminals	<a href="#">Pads</a>
Primary Taps	<a href="#">N/A</a>
Conductor Material	<a href="#">Aluminum</a>
Insulation Class	<a href="#">220°C (Class H)</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">N/A</a>
Impedance Range	<a href="#">2.5 – 4.5%</a>
Sound (db)	<a href="#">55</a>
Enclosure Type	<a href="#">NEMA 3R Indoor</a>
Enclosure Size	<a href="#">E3R-7</a>
Finish/Colour	<a href="#">Polyester Powder Coat – ANSI/ASA 61 Grey</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>



OFFICIAL QUOTE

112KVA 347 VOLTS TO 110 VOLTS  
THREE PHASE AUTOTRANSFORMER



Country/Manufacturer

[Canada/RPM](#)