

OFFICIAL QUOTE

225KVA 440 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER





225KVA 440 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER


\$15,597.80 CAD


Three Phase Autotransformer with a capacity of 225kVA, transforming 440Y Volts to 115Y Volts

SKU: RA225H2-A1

Categories: Autotransformer

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES





Three Phase Autotransformer with a capacity of 225kVA, transforming 440Y Volts to 115Y Volts



OFFICIAL QUOTE



225KVA 440 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER

PRODUCT SPECIFICATIONS

| PRODUCT SPECIFICATIONS | |
|----------------------------|--|
| Weight | 1095 lbs |
| Phases | <u>3</u> |
| kVA | 225 |
| Connection | 3PhA-NT-1 |
| Primary Voltage | 440 |
| Primary Max Current | 295.2A |
| Primary Markings | <u>H1-H2-H3</u> |
| Primary Terminals | <u>Pads</u> |
| Secondary Voltage | 115 |
| Secondary Max Current | 1129.6A |
| Secondary Markings | <u>X1-X2-X3</u> |
| Secondary Terminals | <u>Pads</u> |
| Primary Taps | N/A |
| Conductor Material | <u>Aluminum</u> |
| Insulation Class | 220°C (Class H) |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency (@35% Load) % | N/A |
| Impedance Range | <u>2.5 - 4.5%</u> |
| Sound (db) | 60 |
| Enclosure Type | NEMA 3R Indoor |
| Enclosure Size | <u>E3R-8</u> |
| Finish/Colour | Polyester Powder Coat – ANSI/ASA 61 Grey |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered |



OFFICIAL QUOTE

225KVA 440 VOLTS TO 115 VOLTS THREE PHASE AUTOTRANSFORMER



| Country/Manufacturer | Canada/RPM |
|----------------------|------------|
|----------------------|------------|