

OFFICIAL QUOTE

75HP 400 VOLTS THREE PHASE MOTOR STARTER





75HP 400 VOLTS THREE PHASE MOTOR STARTER


\$1,578.00 CAD

Three Phase Motor Starter with a capacity of 75HP, suitable for 400 Volt Systems

SKU: RS75G1

Categories: Motor Starting Autotransformers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Motor Starter with a capacity of 75HP, suitable for 400 Volt Systems



OFFICIAL QUOTE





PRODUCT SPECIFICATIONS

Weight	120 lbs
Phases	3
Connection	3PhA-ST-0-3
Primary Voltage	400
Primary Max Current	N/A
Primary Markings	<u>H1-H2-H3</u>
Primary Terminals	<u>Pads</u>
Secondary Voltage	50/65/80/100%
Secondary Max Current	N/A
Secondary Markings	A-B-C-D
Secondary Terminals	Pads
Primary Taps	N/A
Conductor Material	Copper
Temperatue Rise	<u>150°C</u>
Insuation Class	220°C (Class H)
BIL (Insulation) Level	<u>10kV</u>
Efficiency (@35% Load) %	N/A
Impedance Range	N/A
Sound (db)	N/A
Enclosure Type	Core & Coil
Enclosure Size	N/A (Core & Coil)
Finish/Colour	N/A
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered



OFFICIAL QUOTE



75HP 400 VOLTS THREE PHASE MOTOR STARTER

HP	<u>75</u>
Country/Manufacturer	Canada/RPM