



## 60HP 416 VOLTS THREE PHASE MOTOR STARTER

**\$1,380.00 CAD**

Three Phase Motor Starter with a capacity of 60HP, suitable for 416 Volt Systems

SKU: RS60G

Categories: [Motor Starting Autotransformers](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



Three Phase Motor Starter with a capacity of 60HP, suitable for 416 Volt Systems



## PRODUCT SPECIFICATIONS

Weight	110 lbs
Phases	<a href="#">3</a>
Connection	<a href="#">3PhA-ST-0-3</a>
Primary Voltage	<a href="#">416</a>
Primary Max Current	<a href="#">N/A</a>
Primary Markings	<a href="#">H1-H2-H3</a>
Primary Terminals	<a href="#">Pads</a>
Secondary Voltage	<a href="#">50/65/80/100%</a>
Secondary Max Current	<a href="#">N/A</a>
Secondary Markings	<a href="#">A-B-C-D</a>
Secondary Terminals	<a href="#">Pads</a>
Primary Taps	<a href="#">N/A</a>
Conductor Material	<a href="#">Copper</a>
Temperatue Rise	<a href="#">150°C</a>
Insuation Class	<a href="#">220°C (Class H)</a>
BIL (Insulation) Level	<a href="#">10kV</a>
Efficiency (@35% Load) %	<a href="#">N/A</a>
Impedance Range	<a href="#">N/A</a>
Sound (db)	<a href="#">N/A</a>
Enclosure Type	<a href="#">Core &amp; Coil</a>
Enclosure Size	<a href="#">N/A (Core &amp; Coil)</a>
Finish/Colour	<a href="#">N/A</a>
Standards & Certifications	<a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a>



OFFICIAL QUOTE  
60HP 416 VOLTS THREE PHASE  
MOTOR STARTER



HP	<a href="#">60</a>
Country/Manufacturer	<a href="#">Canada/RPM</a>