



## RS125H

**\$2,221.00 CAD**

SKU: dea648da1085

Categories: [Motor Starters](#)

### SCHEMATIC/DIAGRAM AND DIMENSION PICTURES



### PRODUCT SPECIFICATIONS

|                     |                             |
|---------------------|-----------------------------|
| Weight              | 170 lbs                     |
| Phases              | <a href="#">3</a>           |
| HP                  | <a href="#">125</a>         |
| Connection          | <a href="#">3PhA-ST-0-3</a> |
| Primary Voltage     | <a href="#">480</a>         |
| Primary Max Current | <a href="#">150.4A</a>      |



|                                       |  |
|---------------------------------------|--|
| <b>Primary Markings</b>               | <a href="#">H1-H2-H3</a>   |
| <b>Primary Terminals</b>              | <a href="#">Pads</a>   |
| <b>Secondary Voltage</b>              | <a href="#">50/65/80/100%</a>  |
| <b>Secondary Max Current</b>          | <a href="#">1443.4A</a>  |
| <b>Secondary Markings</b>             | <a href="#">A-B-C-D</a>  |
| <b>Secondary Terminals</b>            | <a href="#">Pads</a>   |
| <b>Primary Taps</b>                   | <a href="#">N/A</a>  |
| <b>Conductor Material</b>             | <a href="#">Copper</a>   |
| <b>Temperatue Rise</b>                | <a href="#">150°C</a>  |
| <b>Insuation Class</b>                | <a href="#">220°C</a>  |
| <b>BIL (Insulation) Level</b>         | <a href="#">10kV</a>   |
| <b>Efficiency</b>                     | <a href="#">N/A</a>  |
| <b>Impedance</b>                      | <a href="#">N/A</a>  |
| <b>Sound (db)</b>                     | <a href="#">N/A</a>  |
| <b>Enclosure Type</b>                 | <a href="#">Core &amp; Coil</a>  |
| <b>Enclosure</b>                      | <a href="#">N/A</a>  |
| <b>Finish</b>                         | <a href="#">N/A</a>  |
| <b>Standards &amp; Certifications</b> | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E108255, ISO 9001:2015 Registered</a> |