


OFFICIAL QUOTE

MP3C9H-M/BO/CLC






MP3C9H-M/BO/CLC


\$8,954.00 USD

SKU: 9751dfb29ca8

Categories: Mini Power Centers

SCHEMATIC/DIAGRAM AND DIMENSION PICTURES







OFFICIAL QUOTE MP3C9H-M/BO/CLC



PRODUCT SPECIFICATIONS

Wataka	215 lb a
Weight	315 lbs
Phases	3
Circuit Breaker Suitability	Eaton Type BAB
kVA	9
Connection	MPC3P-3t
Incoming Voltage	480
Primary Breaker	25A
Interruping Rating	14kAIC @ 480V
Output Voltage	<u>208Y/120</u>
Secondary Breaker	<u>30A</u>
Short Circuit Withstand	10kAIC @ 240V
Primary Taps	<u>+/- 1 x 5%</u>
Conductor Material	Copper
Insuation Class	200°C
Panel Board	Bolt-On
Load Center Bus Material	<u>Copper</u>
# of Circuits	18
Impedance	<u>1.5 - 3.0%</u>
Temperatue Rise	130°C
Enclosure	E3R-3PMPC-1B
Enclosure Type	E3R Outdoor
Finish	Polyster Powder Coat – ANSI/ASA 61 Grey
Standards & Certifications	CSA Certified File No. LR34493, ISO 9001:2015 Registered