



## CE1000B-K

**\$382.23 USD**

SKU: 6c1b98f72a85

Categories: [Control Transformers](#)

### PRODUCT SPECIFICATIONS

|                       |                              |
|-----------------------|------------------------------|
| Weight                | 23 lbs                       |
| Phases                | <a href="#">1</a>            |
| VA                    | <a href="#">1000</a>         |
| Connection            | <a href="#">1Ph-CT-SD-SD</a> |
| Primary Voltage       | <a href="#">208</a>          |
| Primary Max Current   | <a href="#">4.81A</a>        |
| Primary Markings      | <a href="#">H1-H2</a>        |
| Primary Terminals     | <a href="#">Leads</a>        |
| Secondary Voltage     | <a href="#">120/240</a>      |
| Secondary Max Current | <a href="#">8.33A</a>        |
| Secondary Markings    | <a href="#">X1-X2-X3-X4</a>  |



|                                       |  |
|---------------------------------------|--|
| <b>Secondary Terminals</b>            | <a href="#">Leads</a>  |
| <b>Primary Taps</b>                   | <a href="#">N/A</a>  |
| <b>Conductor Material</b>             | <a href="#">Copper</a>   |
| <b>Temperatue Rise</b>                | <a href="#">115°C</a>  |
| <b>Insuation Class</b>                | <a href="#">180°C</a>  |
| <b>BIL (Insulation) Level</b>         | <a href="#">10kV</a>   |
| <b>Efficiency</b>                     | <a href="#">N/A</a>  |
| <b>Impedance</b>                      | <a href="#">5.0 – 7.0%</a>   |
| <b>Sound (db)</b>                     | <a href="#">40</a>   |
| <b>Enclosure Type</b>                 | <a href="#">Type-1 Indoor</a>  |
| <b>Enclosure</b>                      | <a href="#">See Chart</a>  |
| <b>Standards &amp; Certifications</b> | <a href="#">CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered</a> |
| <b>Finish</b>                         | <a href="#">Semigloss – BlackSemigloss – Black</a>   |