





CS150H-L \$157.00 CAD

SKU: 34eba677dd15 Categories: <u>Control Transformers</u>

PRODUCT SPECIFICATIONS

Weight	18 lbs
Phases	1
VA	<u>150</u>
Connection	<u>1Ph-CT-SD-SD</u>
Primary Voltage	<u>480</u>
Primary Max Current	<u>0.31A</u>
Primary Markings	<u>H1-H2</u>
Primary Terminals	<u>Terminals</u>
Secondary Voltage	240/480
Secondary Max Current	<u>0.63A</u>
Secondary Markings	<u>X1-X2-X3-X4</u>

The quote is valid 30 days from 19 April 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



CS150H-L



Secondary Terminals	Terminals
Primary Taps	N/A
Conductor Material	<u>Copper</u>
Temperatue Rise	<u>80°C</u>
Insuation Class	<u>130°C</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency	N/A
Impedance	<u>5.0 – 7.0%</u>
Sound (db)	<u>40</u>
Enclosure Type	Core & Coil
Enclosure	See Chart
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered
Finish	N/AN/A