





CS150H-L \$157.00 CAD

SKU: 34eba677dd15 Categories: Control Transformers

PRODUCT SPECIFICATIONS

| Weight | 18 lbs |
|-----------------------|---------------------|
| Phases | 1 |
| VA | <u>150</u> |
| Connection | <u>1Ph-CT-SD-SD</u> |
| Primary Voltage | <u>480</u> |
| Primary Max Current | <u>0.31A</u> |
| Primary Markings | <u>H1-H2</u> |
| Primary Terminals | <u>Terminals</u> |
| Secondary Voltage | 240/480 |
| Secondary Max Current | <u>0.63A</u> |
| Secondary Markings | <u>X1-X2-X3-X4</u> |

The quote is valid 30 days from 6 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



CS150H-L



| Secondary Terminals | Terminals |
|----------------------------|---|
| Primary Taps | N/A |
| Conductor Material | <u>Copper</u> |
| Temperatue Rise | <u>80°C</u> |
| Insuation Class | <u>130°C</u> |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency | N/A |
| Impedance | <u>5.0 – 7.0%</u> |
| Sound (db) | <u>40</u> |
| Enclosure Type | Core & Coil |
| Enclosure | See Chart |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered |
| Finish | N/AN/A |