





## **CS200H-L** \$128.88 USD

SKU: 26d2acfb01d9 Categories: Control Transformers

## **PRODUCT SPECIFICATIONS**

Weight	23 lbs
Phases	1
VA	200
Connection	<u>1Ph-CT-SD-SD</u>
Primary Voltage	<u>480</u>
Primary Max Current	<u>0.42A</u>
Primary Markings	<u>H1-H2</u>
Primary Terminals	Terminals
Secondary Voltage	240/480
Secondary Max Current	<u>0.83A</u>

The quote is valid 30 days from 9 May 2025. The price does not include: "Special Features", freight and possible taxes. Disclosing this information to the third party or other supplier may lead to the cancellation of this quote. All other requests please email to sales@transformersource.ca. Printed: September-16-2024.



## CS200H-L



Secondary Markings	<u>X1-X2-X3-X4</u>
Secondary Terminals	Terminals
Primary Taps	N/A
Conductor Material	Copper
Temperatue Rise	<u>80°C</u>
Insuation Class	<u>130°C</u>
BIL (Insulation) Level	<u>10kV</u>
Efficiency	N/A
Impedance	<u>5.0 - 7.0%</u>
Sound (db)	<u>40</u>
Enclosure Type	Core & Coil
Enclosure	See Chart
Standards & Certifications	CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered
Finish	N/AN/A