

OFFICIAL QUOTE

CS350K-Z





CS350K-Z

\$184.85 USD

SKU: 9eedd2b9bed3

Categories: Control Transformers

PRODUCT SPECIFICATIONS

| Weight | 40 lbs |
|-----------------------|--------------------|
| Phases | 1 |
| VA | 350 |
| Connection | 1Ph-CT-DD-SD |
| Primary Voltage | 120/240 |
| Primary Max Current | 2.92A |
| Primary Markings | <u>H1-H2-H3-H4</u> |
| Primary Terminals | <u>Terminals</u> |
| Secondary Voltage | 12/24 |
| Secondary Max Current | 29.17A |
| Secondary Markings | X1-X2-X3-X4 |
| Secondary Terminals | <u>Terminals</u> |



OFFICIAL QUOTE

CS350K-Z



| Primary Taps | N/A |
|----------------------------|--|
| Conductor Material | Copper |
| Temperatue Rise | 80°C |
| Insuation Class | 130°C |
| BIL (Insulation) Level | <u>10kV</u> |
| Efficiency | N/A |
| Impedance | <u>5.0 - 7.0%</u> |
| Sound (db) | 40 |
| Enclosure Type | Core & Coil |
| Enclosure | See Chart |
| Standards & Certifications | CSA Certified File No. LR34493, UL Listed File No. E110286, ISO 9001:2015 Registered |
| Finish | N/AN/A |